

## Technische specificaties

Type	S3H18	S4H28
Weight	1250 kg	1900 kg
Engine	18 hp Petrol	28 pk diesel
Working speed	0-12 km/h	
Lifting seats	Manual	Hydraulic
Driven on all wheels	Option	Yes
Hydraulic tilting collection bin	Option	Yes
Track width	1,50 m	1,50 m



## Roguing Cart

*Specially selected for you*

## VSS Machinebouw, voor de volledige pootgoed oogst.



Windrower



Potato topper

### VSS Machinebouw BV

Ovezandseweg 6a  
4436 RE Oudelande  
The Netherlands

T +31 113 567050

E [info@vssmachinebouw.com](mailto:info@vssmachinebouw.com)

I [www.vssmachinebouw.com](http://www.vssmachinebouw.com)

### Your dealer:



Follow us on:

[twitter.com/vssmachinebouw](https://twitter.com/vssmachinebouw)

[facebook.com/vssmachinebouw](https://facebook.com/vssmachinebouw)



## VSS Agro Roguing Cart

The hydraulically driven VSS Agro Roguing Cart has been designed to visually inspect the potato fields for the removal of deviant plants while driving. The deviant plants can be deposited in the 500L plastic collection bin with stainless steel sides. The choice for the materials plastic and stainless steel is easy to explain because they are simple to clean. Every seat contains a failsafe device which will stop the motor in case of an emergency. The seats are extendible to 4,5 meters. The standard version is equipped with a 30L fuel tank and tire size 7.50-16. The track width is 1,50 meters. Starting the engine and all other functions can be operated directly and easily from the operator seat. The VSS Agro Roguing cart is characterised by a neat finish and the ease of use.

### Three wheel VSS Agro Roguing Cart

There's choice between 2 or 3 hydraulic driven wheels. The standard version has 2 seats which can be manually adjusted, vertically and horizontally. The Roguing Cart has a 18 HP petrol engine with electric starter.

### Options three wheel VSS Agro Roguing Cart:

- Hydraulic adjustable seats, vertically and horizontally.
- Electric start/stop function for two seats.
- Hydraulic tilting collection bin.
- Sun caps.
- Haulm guides on front wheels.



### Four wheel VSS Agro Roguing Cart

This roguing cart is equipped with 4 hydraulic driven wheels. The standard version has two seats which can be hydraulically adjusted, vertically and horizontally. The 4 wheel VSS Agro Roguing Cart has a 28 HP low-noise and low-emission diesel engine with electric starter. Major advantage of the four wheel roguing cart is the stability and improved functioning in wet soil compared to the three wheel roguing cart.

### Options four wheel VSS Agro Roguing Cart:

- Hydraulic adjustable third seat, vertically.
- Electric start/stop function for the third seat.
- Luxury adjustable seats.
- Hydraulic adjustable seats up to 6m.
- Track width 1,80 meters.
- Large wheels 7.50 – 20.
- Sun caps.
- Large lockable storage bin.
- Haulm guides on front wheels.
- Cruise control.
- GPS speed (only available in combination with cruise control).

1 Compactly built

2 Three wheel roguing cart

3 Diesel engine

4 Petrol engine

5 Hydraulic tilting collection bin

6 Remote control

7 Hydraulic adjustable seats (up to 4,5m)

8 Hydraulic adjustable seats (up to 6m)

9 Operation panel with Cruise Control

10 Large wheel covers

DETAILS

